


NO	Product name	Model specification	Remarks
1	PE010405	H05VV-F 3G0.75mm ² *0.5M	Black
2	PE010410	H05VV-F 3G0.75mm ² *1.0M	Black
3	PE010418	H05VV-F 3G0.75mm ² *1.8M	Black
4	PE010430	H05VV-F 3G1.0mm ² *3.0M	Black
5	PE010450	H05VV-F 3G1.0mm ² *5.0M	Black
6	PE010430W	H05VV-F 3G1.0mm ² *3.0M	White
7	PE010450W	H05VV-F 3G1.0mm ² *5.0M	White

Notes:

- Cable:H05VV-F 3G0.75mm²Jacket $\phi 6.5 \pm 0.1$ Conductor 24*0.198
H05VV-F 3G1.0mm²Jacket $\phi 7.0 \pm 0.1$ Conductor 32*0.198
- Mark: \triangleleft VDE \triangleright H05VV-F 3G0.75mm² SHANGYU JINTAO ELECTRON CO.,LTD
 \triangleleft VDE \triangleright H05VV-F 3G1.0mm² SHANGYU JINTAO ELECTRON CO.,LTD
- Test:Hi-pot:Inner Voltage AC2500V/1S External Voltage AC4500V/1S
current leakage 1mA,insulation resistance no less than 50M Ω ,no strike out;



5.		ACCORDING	DIN VDE 0620 - 1		MATERIAL	PVC	
4.			IEC60320		RATED	16A 250V ~ /10A 250V ~	
3.	JT-ST3	DRAWER		EDITION	A4	Dr.No.	
2.	WIRE	REVIEW			COLOR		
1.	JT003 Plug to the European standard	APPROVE	Zhang		2019-7-8	ALL DIMENSIONS IN mm	
PART	DESCRIPTION	DO NOT SCALE	DATE				