



USB 3.1 SuperSpeed+ Kabel

Anschlüsse: USB 3.1 Typ C-Stecker >
USB 3.0 A-Buchse

Material: Isolation: PE, PVC
Innenleiter: CU; AWG 28/32/34

max. Datenrate: 5 Gbit/s

USB-Standard: USB3.1/3.0,

Kompatibilität: USB2.0, 1.1

Spannungsfestigkeit: DC 300 V

Isolationswiderstand: 10 MΩ

Kontaktwiderstand: 2 Ω

RoHS-konform

USB 3.1 SuperSpeed+ cable

Connectors: USB 3.1 Type C plug >
USB 3.0 A jack

Material: Insulation: PE, PVC
Inner conductor: CU; AWG 28/32/34

max. data rate: 5 Gbit/s

USB standard: USB3.1/3.0,

Compatibiliy: USB2.0, 1.1

Dielectric strength: DC 300 V

Insulation resistance: 10 MΩ

Contact resistance: 2 Ω

RoHS compliant

Änderungen

Datum	Name	gez.:	Datum	Name	Bezeichnung	Blatt
		gef.:	31.01.2015	tf	USB 3.1 ADAP C-M/A-F 3.0	I
		gepr.:	31.01.2015	tf		
		Norm:	Änderungen vorbehalten / Subject to change			von
			67894			J

