



- USB 3.0 SUPER SPEED KABEL
- USB A-Stecker > USB A-Buchse
- Bitrate: bis zu 5Gb/s
- Schirmung: 3-fach
- Isolationswiderstand: 300V 10MOhm
- Spannungsfestigkeit: AC 150V~/s, 1mA
- Kabelaufdruck: E324703 **900**
- AWM STYLE 2725 80°C 30V
- Kontaktwiderstand: 30Ohm
- Innenleiter: AWG 28, Cu
- Isolation: 88A PVC
- RoHS-konform

Nr. / No.	Länge / Length (m)
93998	1.80
93999	3.00
95726	5.00

- USB 3.0 SUPER SPEED CABLE
- USB A plug > USB A jack
- Bit rate: up to 5Gbps
- Shielding: 3 times
- Insulation resistance: 300V 10MOhm
- Dielectric strength: AC 150V~/sec., 1mA
- Imprint: E324703 **900**
- AWM STYLE 2725 80°C 30V
- Contact resistance: 30Ohm
- Inner conductor: AWG 28, Copper
- Insulation: 88A PVC
- RoHS compliant



Änderungen		Datum	Name	Bezeichnung	Blatt
Datum	gez.:	28.11.2013	tf	USB 3.0 Verl AA SCHWARZ	900bay®
	gepr.:	28.11.2013	tf		
	Norm:				
Änderungen vorbehalten / Subject to change		Zeichnungs-Nr.:			