

MPN: HDM191930V2.1OP

# Premium Optic Fiber HDMI 2.1 Cable

## 30m

This active optical HDMI 2.1 cable connects devices across long distances up to 100m without data loss – even in sensitive applications. It contains both fiber optic and copper cores, it is lightweight, flexible and has an ultra-small bend radius which makes it perfectly suitable for all kinds of installations.



- Supporting 8K60Hz, 48Gbps
- Sampling : YUV 4:4:4
- Outer Diameter: 4,5mm, very flexible
- Compatible with HDMI 2.1 standard
- Supports EDID, CEC, HDCP (2.2), HDR (High Dynamic Range ), HEC, eARC
- Hybrid optical cable with fibre and copper wire
- Has Source & Display clearly printed on the connector for easy identification
- No loss of signal – delivering crystal clear digital images instantly
- Low RFI / EMI profile for sensitive applications
- Has high pulling strength and compression load

## Specifikationer

Features	3D	Y
Audio Return Channel (ARC)	Y	
Cable length	30 m	
Cable material	Copper	
Connector 1	HDMI Type A (Standard)	
Connector 1 form factor	Straight	
Connector 1 gender	Male	
Connector 2	HDMI Type A (Standard)	
Connector 2 form factor	Straight	
Connector 2 gender	Male	
Connector contacts plating	Gold	
Data transfer rate	48 Gbit/s	
Dolby technologies	Dolby TrueHD	
HDCP	Y	
HDCP version	1.4/2.2	
HDMI version	2.1	
High Dynamic Range (HDR) supported	Y	
Maximum refresh rate	120 Hz	
Maximum resolution	7680 x 4320 Pixels	
Plug and Play	Y	
Product colour	Black	
Quantity per pack	1 pc(s)	
RoHS compliance	Y	

<b>Features</b>	<b>Supported video modes</b>	480p, 720p, 1080i, 1080p, 2160p, 4320p
<b>Other features</b>	<b>Quantity</b>	1
<b>Package dimensions (verified)</b>	<b>Depth Verified</b>	22,9 cm
	<b>Gross Weight Verified</b>	1,168 kg
	<b>Height Verified</b>	7,9 cm
	<b>Width Verified</b>	24,1 cm
<b>Product dimensions</b>	<b>Net Weight (Product, kg)</b>	1,0679999999999998 kg
<b>Vendor information</b>	<b>Brand Name</b>	MicroConnect
	<b>Warranty</b>	25 År
<b>Weight &amp; dimensions</b>	<b>Cable diameter</b>	4,5 mm

## Andra bilder

